


# EVG Product Overview

01/2015

Secondary current	voltage	Primary current	Type designation	Order number	Dimensions (mm)			Housing no.	
					Length	Width	Height		
<b>20 mA</b>	990 volts	0.20 A	<b>EVG 20/1SL</b>	1 2010 266	160	29	25	1	●
	2,000 volts	0.25 A	<b>EVG 20/2SL</b>	1 2020 266	160	29	25	1	●
	2,000 volts		<b>EVG 20/2SLR</b>	1 2020 276	160	29	25	1	●
	3,000 volts	0.35 A	<b>EVG 20/3</b>	1 2030 200	160	40	35	2	●
	4,000 volts	0.50 A	<b>EVG 20/4</b>	1 2040 200	170	53	44	6	●
	5,000 volts	0.55 A	<b>EVG 20/5D</b>	1 2050 202	205	39	37	3	●
<b>30 mA</b>	2,000 volts	0.40 A	<b>EVG 30/2</b>	1 3020 200	160	40	35	2	●
	4,000 volts	0.60 A	<b>EVG 30/4</b>	1 3040 200	170	53	44	6	●
<b>40 mA</b>	990 volts	0.25 A	<b>EVG 40/1SL</b>	1 4010 266	160	29	25	1	●
	2x990 volts	0.45 A	<b>EVG 40/1Duo</b>	1 4010 215	185	47	26	5	●
	1,500 volts	0.35 A	<b>EVG 40/1.5</b>	1 4015 200	160	40	35	2	●
	3,000 volts	0.60 A	<b>EVG 40/3</b>	1 4030 200	170	53	44	6	●
<b>50 mA</b>	990 volts	0.35 A	<b>EVG 50/1</b>	1 5010 200	160	40	35	2	●
	2,500 volts	0.60 A	<b>EVG 50/2.5</b>	1 5025 200	170	53	44	6	●
	4,000 volts	0.80 A	<b>EVG 50/4</b>	1 5040 200	255	57	47	13	●
<b>60 mA</b>	990 volts	0.40 A	<b>EVG 60/1</b>	1 6010 200	160	40	35	2	●
	2,000 volts	0.60 A	<b>EVG 60/2</b>	1 6020 200	170	53	44	6	●
<b>80 mA</b>	990 volts	0.45 A	<b>EVG 80/1</b>	1 8010 200	160	53	44	6	●
	1,500 volts	0.60 A	<b>EVG 80/1.5</b>	1 8015 200	160	53	44	6	●
<b>Dimmable EVGs via reverse phase control</b>									
<b>40 mA</b>	990 volts	0.25 A	<b>EVG 40/1D</b>	1 4010 202	205	39	37	7	●
	2x990 volts	0.50 A	<b>EVG 40/1D Duo</b>	1 4010 212	205	49	29	8	●
<b>80 mA</b>	990 volts	0.50 A	<b>EVG 80/1D</b>	1 8010 202	205	39	37	7	●
	2x990 volts	0.95 A	<b>EVG 80/1D Duo</b>	1 8010 215	205	56	38	9	●
<b>Dimmable EVGs via control voltage (0-10 volts)</b>									
<b>40 mA</b>	3,000 volts	0.60 A	<b>EVG 40/3D</b>	1 4030 002	260	62	46	10	●
<b>50 mA</b>	2,000 volts	0.60 A	<b>EVG 50/2D</b>	1 5020 002	260	62	46	10	●
<b>EVGs with integrated flasher unit</b>									
<b>20 mA</b>	5,000 volts	0.55 A	<b>EVG 20/5B</b>	1 2050 204	205	39	37	11	●
	8,000 volts	0.95 A	<b>EVG 20/8B</b>	1 2080 204	207	52	46	11	●

dimmmable via poti



● suitable for blue discharge tubes only   ● suitable for red discharge tubes only   ● suitable for blue and red discharge tubes

Technical modifications reserved. January 2015 Content is protected by copyright. Source: www.hansen-led.com